


S2345-4C42T-GS





DIMENSIONS			BASE MODEL NO.	ADD LAMP CODE	ADD FINISH CODE
W	H	X			
24"	36"	6-1/2"	S2345	4N60	BA, PT
				4C13E	
				4C26E	
				*4C42T	
30"	36"	7-1/24"	S2346	4N100	
				*6C42T	
36"	48"	8-1/2"	S2347	6N100	
				*8C42T	

ORDERING INFORMATION

Order as a Complete Unit: Model No. + Lamp Code + Finish Code + Option Code + Voltage

TECHNICAL SPECIFICATIONS FINISHES OPTIONS

Ballast:	High Power Factor, Electronic, 120/277	BA	Brushed Aluminum	EM	Emergency Battery Pack with Fluorescent Lighting (Integral or Remote)
Mounting:	Mounts to all Standard Electrical Junction Boxes (by others) with Hardware Provided	PT	Painted Finishes – (Specify Color Code from Our Standard Finish Chart)	OA	Specify Overall Height of Fixture in Inches; E.G. – OA48
				DIM	Dimmable Integral Ballast (Consult Factory)
				2C	Two-Circuit Wiring

LAMPING FEATURES

N60	= 60 Watt A19 Incandescent	● Sandblasted Acrylic Bottom Lens
N100	= 100 Watt A19 Incandescent	● Solid Spun Aluminum Shade (Seamless)
C13E	= 13 Watt Quad Tube Compact Fluorescent 4 Pin Electronic, G24Q-1 Base	● Clear Braided SJT Electrical Cord
C26E	= 26 Watt Quad Tube Compact Fluorescent 4 Pin Electronic, G24Q-3 Base	● 5/8" Tube with Stainless Steel Cable
C42T	= 42 Watt Triple Tube Compact Fluorescent 4 Pin Electronic, GX24Q-4 Base	
		* Configuration operates C26T, C32T or C42T lamp options and can be labeled up to the highest wattage allowed

